



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

07.01.2016

revision

13.02.2015 (GB) Version 1.1

WEICON BR Resin

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product

WEICON BR Resin

Code-Nr. 104201

1.2. Relevant identified uses of the substance or mixture and uses advised against

! Recommended intended purpose(s)

2-Component Epoxy Resin - Resin Component

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Postbox 48045, DE-8460 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail : msds@weicon.de

Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0

E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

GIZ Bonn (German, English) Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

Manufacturer

WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

Emergency advice

-

Phone -

GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)

Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

! SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315	
---------------	------	--

Eye Irrit. 2	H319	
--------------	------	--

Skin Sens. 1	H317	
--------------	------	--

Aquatic Chronic 2	H411	
-------------------	------	--

Hazard Statements

H315

Causes skin irritation.

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements**Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]**

GHS07



GHS09

! Signal word

Warning

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P501	Dispose of contents/container to hazardous or special waste collection point.

! Hazardous ingredients for labelingreaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)**! Special rules for supplemental label elements for certain mixtures**

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards**! Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**! SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

3.2. Mixtures**Description**

Bisphenol-A-epoxy resin

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25 < 35	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
7727-43-7	231-784-4	barium sulphate, natural	25 < 35	

REACH

CAS No	Name	REACH registration number
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26-xxxx

! SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

! In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

! In case of ingestion

Do not induce vomiting.

If swallowed by mistake drink plenty of water and seek medical treatment.

Rinse out mouth thoroughly with water.

4.2. Most important symptoms and effects, both acute and delayed**! Physician's information / possible symptoms**

vomiting

Respiratory complaints

Nausea

skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

No information available.



! SECTION 5: Firefighting measures

5.1. Extinguishing media

! Suitable extinguishing media

Fire-extinguishing activities according to surrounding.

5.2. Special hazards arising from the substance or mixture

Metal oxides

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Sulphur dioxide (SO₂)

5.3. Advice for firefighters

! Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

! Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

! SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Do not allow to dry out.

Take up residues with absorbent material (e.g. sand, sawdust, general-purpose binder).

After taking up the material dispose according to regulation.

! Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

! SECTION 7: Handling and storage

7.1. Precautions for safe handling

! Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

**! Hygiene measures**

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

! Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in closed original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

! Further information on storage conditions

Store at +5 till +25 °C.

Keep container tightly closed, store at cool and aired place, open and handle carefully.

Protect from heat and direct solar radiation.

Store in a dry place.

7.3. Specific end use(s)**! Recommendation(s) for intended use**

See section 1.2

! SECTION 8: Exposure controls/personal protection**8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
7727-43-7	Barium sulphate: respirable dust	8 hours	4		EH40/2005
7727-43-7	Barium sulphate: total inhalable dust	8 hours	10		EH40/2005

! Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls**! Respiratory protection**

Selection of the appropriate filter type depends on the quantity and chemicals handled at the workplace. Contact supplier of respiratory protective equipment or more information about filter properties.

In case of insufficient ventilation or long-term effect use breathing apparatus.

Breathing apparatus in the event of aerosol or mist formation.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min;

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

! Eye protection

tightly fitting goggles

! Other protection measures

protective clothing



Appropriate engineering controls
Sufficient ventilation and exhaustion.

! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

pasty

Colour

dark brown

Odour

uncharacteristic

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not applicable				
boiling point	not determined				
melting point	not determined				
Flash point	not applicable			closed cup	
Vapourisation rate	not applicable				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	not applicable				
Upper explosion limit	not applicable				
Vapour pressure	not determined				
Relative density	ca. 1,87 g/cm ³				
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not applicable	20 °C			
Viscosity kinematic	not determined				

**Oxidising properties**

No information available.

Explosive properties

not applicable

9.2. Other information

No information available.

! SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Evolution of heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Toxic gases/vapours

Metaloxides

Sulphurous oxides (SO_x)**Thermal decomposition**

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
Skin irritation	irritant	rabbit		CAS: 25068-38-6
Eye irritation	irritant	rabbit eye		CAS: 25068-38-6
Skin sensitization	sensitizing			

! Experiences made from practice

Sensitization through skin contact possible.

Irritates eyes and skin.

! Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.



! SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

	Value	Species	Method	Validation
Algae	EC50 634 mg/l (48 h)	Cypris subglobosa		CAS: 7727-43-7

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

Additional ecological information

	Value	Method	Remark
AOX	The product contains organically halogen, it can contribute to the adsorbable organic halogen value.		

! General regulation

Toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

! SECTION 13: Disposal considerations

13.1. Waste treatment methods

! Waste code No.

08 04 09*

Name of waste

waste adhesives and sealants containing organic solvents or other hazardous substances

15 01 10*

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

! Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

! Recommendations for packaging

Packaging that cannot be cleaned should be disposed of like the product.

! General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3082	3082	3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (Epoxy-Harz)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy-resin)	Environmentally hazardous substance, liquid, n.o.s. (epoxy-resin)
14.3. Transport hazard class(es)	9	9	9
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes	Yes	Yes
14.6. Special precautions for user	No information available.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	not applicable		
Land and inland navigation transport ADR/RID	Hazard label(s) 9 tunnel restriction code E Classification code M6		
Marine transport IMDG	MARINE POLLUTANT		

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information**! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.0

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.



Safety Data Sheet according to Regulation (EC)
No. 1907/2006 (REACH)

Printed

07.01.2016

revision

13.02.2015 (GB) Version 1.1

WEICON BR Resin

H411 Toxic to aquatic life with long lasting effects.