

顶级润滑喷剂



安全与健康

使用WEICON产品时，需注意产品的物理性、安全性、毒理性、生态性的详细参数以及我们EG材料安全数据表（www.weicon.com）的具体信息。

包装

11510400-47 顶级润滑喷剂 400 ml

蠕变性能极其突出

顶级润滑喷剂是一款透明、合成的粘附性润滑剂。它适用于所有高强度的机器部件，效果持久。

顶级润滑喷剂附着力极好，蠕变性能出色，能耐压、防水，耐温-40至+200°C。在严格遵守安全操作规程的前提下，该产品亦可使用于运行中的设备。

该产品不会腐蚀如PTFE、PE、PA、氟化、丁二烯和硅橡胶、聚氯丁烯等的塑料材质及弹性体。在特定条件下，该产品可用于PELD、POM、PP、NBR。

WEICON 顶级润滑喷剂可用于动力传动皮带、齿轮、蜗轮、快速运行机器零件、接头、联轴器、滚轴、滚珠轴承和弹簧组件。

技术参数

气味	矿物油
特色	蠕变性能出色，可驱水
保存期限	24 个月
颜色	无色
运动粘度 (+40°C DIN 51562)	79 mm²/s
运动粘度 (+100°C DIN 51562)	9 mm²/s
耐温性	-40 至 +200 °C
ISSA 编码	53.402.12
IMPA 编码	450826

操作

使用前请用力摇晃瓶身。将该喷剂置于距清洁、干燥的物体表面约15cm处进行喷洒。第一次使用过后，亦可在遵守相关安全规定的前提下，在机器运转时使用该喷剂。

储藏

容器带压。避免阳光直射。储存温度不可超过+50°C。

提示

本资料中列出的所有产品，其参数和建议是我们在实验室的测试结果及经验总结，不得被视为对产品特性的保证。由于每一个用的实际应用情况并不在我们的认知、控制及责任范围内，我们对这些信息并不承担任何义务。我们保证我们的产品符合并遵守我们销售条款中承诺的高品质、无瑕疵的要求。我们建议用户通过自行试验来论证其希望选用的产品是否完全符合预期。因用户未遵照指定的操作方法使用产品而造成损失的情况，用户将独自承担全部责任。

WEICON GmbH & Co. KG
(Headquarters)
Germany
phone +49 (0) 251 9322
0
info@weicon.de
www.weicon.de

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709
0088
info@weicon.co.za
www.weicon.co.za

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae
www.weicon.ae

WEICON South East Asia Pte Ltd
Singapore
phone (+65) 6710 7671
info@weicon.com.sg
www.weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca
www.weicon.ca

WEICON Czech Republic
s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz
www.weicon.cz

WEICON Kimya Sanayi Tic. Ltd.
Şti.
Turkey
phone +90 (0) 212 465 33 65
info@weicon.com.tr
www.weicon.com.tr

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es
www.weicon.es

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730
763
office@weicon.com
www.weicon.com.ro

WEICON Italia S.r.l.
Italy
phone (+39) 0102924871
info@weicon.it
www.weicon.it

Top-Lube



also while parts to be lubricated are in operation, subject to respect of the relevant safety regulations.

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

11510400 Top-Lube 400 ml

excellent creeping properties

Top-Lube is a synthetic, transparent adhesive lubricant for the permanent lubrication of all types of highly stressed mechanical parts.

WEICON Top-Lube has a high adhesive and spinning strength and outstanding creeping properties. It is pressure-resistant, water-rejecting and can also be used during on-going operation in compliance with the respective safety regulations.

It does not attack the following plastics and elastomers: PTFE, PE, PA, fluorinated - , butadiene and silicone rubber, and polychloroprene. The following materials have a limited resistance: PE-LD, POM, PP, NBR.

WEICON Top-Lube can be used to force-transmitting bolts, gears and worm gears, high-speed machinery parts, joints and couplings, wheels and bearings and spring assemblies in many industrial sectors.

Technical Data

Odour	mineral oil
Features	water-repellent, excellent creep properties
Silicone free	yes
Storage stability	24 months
Colour	colourless
Kinematic viscosity (DIN 51562) at +40°C	79 mm²/s
Kinematic viscosity (DIN 51562) at +100°C	9 mm²/s
Temperature resistance	-40 to +200 °C
ISSA-Code	53.402.12
IMPA-Code	450826

Processing

Surfaces to be treated must be clean and dry. Shake can and spray at about 15 cm from surface. Product may, thereafter, be applied

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG
(Headquarters)
Germany
phone +49 (0) 251 9322 0
info@weicon.de
www.weicon.de

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae
www.weicon.ae

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca
www.weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.
Turkey
phone +90 (0) 212 465 33 65
info@weicon.com.tr
www.weicon.com.tr

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com
www.weicon.com.ro

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za
www.weicon.co.za

WEICON South East Asia Pte Ltd
Singapore
phone (+65) 6710 7671
info@weicon.com.sg
www.weicon.com.sg

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz
www.weicon.cz

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es
www.weicon.es

WEICON Italia S.r.l.
Italy
phone (+39) 0102924871
info@weicon.it
www.weicon.it